

High Performance Products Physical & Design Data

Glass Block	Actual Block Size ¹	Weight of glass block (lb)	Approximate Installed Weight (lb/ft ²)	Number pieces/sq.ft.	Heat Transmission ² U-Value (BTU/hr ft ² °F)	Thermal Resistance ² R-value (hr ft ² °F/ BTU)	Visible Light Transmission ³ (%)	Shading Coefficient ⁴	Sound transmission S.T.C. (dB)	Solar Heat Gain Coefficient ⁵ (%)	Fire rating
THICKSET® Products											
6x6x4 Clarity THICKSET® 90	5-3/4" x 5-3/4" x 3-7/8"	5.5	23.7	4	0.51	1.96	75	.65	48	.66-.68 ⁵	90
8x8x4 Clarity THICKSET® 60	7-3/4" x 7-3/4" x 3-7/8"	7.8	22.7	2.25	0.51	1.96	75	.65	48	.66-.68 ⁵	60
8x8x4 Clarity THICKSET® 90	7-3/4" x 7-3/4" x 3-7/8"	10.6	25.5	2.25	0.51	1.96	75	.65	50	.66-.68 ⁵	90
8x8x4 Nubio THICKSET® 60	7-3/4" x 7-3/4" x 3-7/8"	7.8	22.7	2.25	0.51	1.96	75	.65	48	.66-.68 ⁵	60
8x8x4 Nubio THICKSET® 90	7-3/4" x 7-3/4" x 3-7/8"	10.6	25.5	2.25	0.51	1.96	75	.65	50	.66-.68 ⁵	90
8x8x4 Spray THICKSET® 60	7-3/4" x 7-3/4" x 3-7/8"	7.8	22.7	2.25	0.51	1.96	75	.65	48	.66-.68 ⁵	60
8x8x4 Endura THICKSET® 90	7-3/4" x 7-3/4" x 3-7/8"	10.6	25.5	2.25	0.51	1.96	75	.65	50	.66-.68 ⁵	90
8x8x3 VistaBrik	7-5/8" x 7-5/8" x 3"	15.4	40	2.25	0.7	1.42	90	49.4	53	.75-.78 ⁵	90
8x8x3 VistaBrik Stipple	7-5/8" x 7-5/8" x 3"	15.4	40	2.25	0.7	1.42	83	49.4	53	.75-.78 ⁵	90
6x8x3 VistaBrik	5-5/8" x 7-5/8" x 3"	9.9	33	3	0.7	1.42	90	49.4	53	.75-.78 ⁵	90
4x8x3 VistaBrik	3-5/8" x 7-5/8" x 3"	7.9	39	4.5	0.7	1.42	90	49.4	53	.75-.78 ⁵	90
Vetropieno™ Products											
Neutro Rettangolare	4.60" x 2.125" x 9.45"	7.7	51.8	5.8	0.62	1.61	44	58.6	43	51	90
Nuetro Quadrato	4.625" x 2.125" x 4.725"	3.7	51.2	11.2	0.62	1.61	44	58.6	43	51	90
Blu Rettangolare	4.60" x 2.125" x 9.45"	7.7	51.8	5.8	0.62	1.61	7	42.5	43	37	90
Blu Quadrato	4.625" x 2.125" x 4.725"	3.7	51.2	11.2	0.62	1.61	7	42.5	43	37	90
Nordica Rettangolare	4.60" x 2.125" x 9.45"	7.7	51.8	5.8	0.62	1.61	2	39.1	43	34	90
Nordica Quadrato	4.625" x 2.125" x 4.725"	3.7	51.2	11.2	0.62	1.61	2	39.1	43	34	90
Siena Rettangolare	4.60" x 2.125" x 9.45"	7.7	51.8	5.8	0.62	1.61	8	40.2	43	35	90
Siena Quadrato	4.625" x 2.125" x 4.725"	3.7	51.2	11.2	0.62	1.61	8	40.2	43	35	90
Vetropieno™ - Americano Products											
Neutro Rettangolare	3.675" x 2.250" x 7.675"	5.29	51.7	8.4	0.62	1.61	44	58.6	43	51	90
Nuetro Quadrato	3.675" x 2.250" x 3.750"	2.64	52.5	17.1	0.62	1.61	44	58.6	43	51	90

¹Size-Blocks are manufactured to a 1/16" (2mm tolerance)
²Heat Transmission/Thermal Resistance: Winter night values. To calculate instantaneous heat gain through glass panels, see ASHRAE HANDBOOK OF FUNDAMENTALS.
³Light Transmission-Values +/-5%
⁴Light Transmission/Shading Coefficient-Estimated figures based on accumulated data.
⁵Shading Coefficient-Based on 8"-sq. unit; ratio of heat gain through glass block panels vs. that through a single light of double-strength sheet glass under specific conditions.

Seves Glass Block has a sales and technical support team that is ready to help you design, engineer and specify glass block solutions. Please visit our website at sevesglassblockinc.com




SEVES GLASS BLOCK INC.
 SPRINGFIELD, IL 62704
 1-440-627-6257
 TOLL FREE 1-877-SEVES11

INQUIRY@SEVESGLASSBLOCK.COM

SEVES
 GLASS
 BLOCK

FIRE-RATED GLASS BLOCK

PREMIERE™ SERIES · THICKSET® 45, 60, 90 · VISTABRIK · VETROPIENO



CREATE MORE.

GLASS BLOCK FOR FIRE PROTECTION

Seves Glass Block manufactures Glass Block through a simple, yet exacting process and maintains the highest quality standards to produce a unique building material – virtually a brick made of glass. The special combination of properties increases design flexibility and provides many functional benefits. The material offers transparency, emitting generous amounts of natural or borrowed light while at the same time providing energy efficiency, sound control, security, and visual texture. When patterned, Glass Block offers a unique combination of privacy and light transmission.

An extremely important feature of Glass Block, critical to safe building design, is the products inherent fire-resistance property. By varying the face thickness of the product and conforming to installation specifications, Seves Glass Block offers a family 45 and 60 minute fire rated products that conform with UL-9 or NFPA 257 standards for window assemblies. Our 90 minute rated products are tested to NFPA 257 and are certified by National Accreditation and Management Institute (NAMI) as window assemblies. With Vetropieno, our newest addition to our fire rated glass block family. This solid glass brick provides up to a 90-minute fire rating in a window assembly without sacrificing aesthetics, design, flexibility, light transmission or privacy. In addition, these products can be specified in different patterns or colors to meet your design needs.

Our Family of Fire-Rated Glass Block and Solid Glass Brick Products



4" PREMIERE™ SERIES

- The Premiere™ Series includes the largest selection of patterns, sizes and shapes for the utmost in design flexibility.
- All patterns of Premiere™ Series Glass Block are classified by UL for use in 45-minute-rated window assemblies.
- Available patterns: Alpha, Argus, Clarity, Cortina, Cross Ribbed, Light Diffusing, Nubio, Tartan.
- Available Sizes: All sizes except 12" x 12" and shapes.
- Nominal face thickness = 0.25"
- Sound Transmission Class (S.T.C.) = 39
- Frosted finish available for added privacy.



THICKSET® 90

- The THICKSET® 90 Glass Block is a thicker-faced block that provides all the traditional benefits of glass block plus a 90-minute fire rating.
- THICKSET® 90 Block is approved by UL-9 and NFPA 257 standards for use in 45-, 60- or 90- minute-rated window assemblies.
- Available patterns: NUBIO, ENDURA, and CLARITY
- Available in Frosted for added privacy.
- Available Sizes: 6" x 6" x 4" CLARITY 8" x 8" x 4" NUBIO, ENDURA and CLARITY
- Nominal face thickness = 0.75"
- Sound Transmission Class (S.T.C.) = 50



THICKSET® 60

- The THICKSET® 60 Glass Block is a thicker-faced block that provides all the traditional benefits of glass block plus a 60-minute fire rating.
- THICKSET® 60 Block is certified UL-9 and NFPA 257 standards for use in 45- or 60- minute-rated window assemblies.
- Available patterns: NUBIO, CLARITY, SPRAY
- Available Sizes: 8" x 8" x 4"
- Nominal face thickness = 0.375"
- Sound Transmission Class (S.T.C) = 48
- Frosted finish available for added privacy.



VISTABRIK® 90

- VISTABRIK® Solid Glass Block is the ultimate glass block solution, 3 solid inches of glass which resists bullets, fire, noise, graffiti, and forcible entry.
- VISTABRIK® Solid Glass Block is approved by UL-9 and NFPA 257 standards for use in 45-, 60- or 90-minute rated window assemblies.
- Available patterns: Clear – for good visibility or Stippled or Frosted for added privacy.
- VISTABRIK® Solid Glass Block are bullet resistant.
- Available Sizes: 8" x 8" x 3", 4" x 8" x 3", 6" x 8" x 3"
- Actual face thickness = 3.0"
- Sound Transmission Class (S.T.C.) = 53



Vetropieno™

- Provides a 90 minute fire rating. 100% solid glass bricks in clear and 3-designer colors. Glass bricks deliver a unique visual and light transparency unlike those of standard hollow brick.
- VETROPIENO™ Solid Glass Brick is certified UL-9 and NFPA 257 standards for use in 45-, 60- or 90-minute rated window assemblies.
- Vetropieno™ Rettangolare: 4.60" x 2.125" x 9.45"
- Vetropieno™ Quadrato: 4.625" x 2.125" x 4.725"
- Nominal face thickness = 3.0"
- Sound Transmission Class (S.T.C) = 53



Vetropieno™ Americano

- Provides a 90 minute fire rating. 100% solid glass bricks in clear. Glass bricks deliver a unique visual and light transparency unlike those of standard hollow brick. Available in Clear only.
- VETROPIENO™ AMERICANO Solid Glass Brick is certified UL-9 and NFPA 257 standards for use in 45-, 60- or 90-minute rated window assemblies.
- Vetropieno™ Americano Rettangolare: 3.675" x 2.250" x 7.675"
- Vetropieno™ Americano Quadrato: 3.675" x 2.250" x 3.750"
- Nominal face thickness = 3.0"
- Sound Transmission Class (S.T.C) = 53

Functional Benefits of Glass Block

• Fire Resistant

Certified by Underwriters Laboratory (UL) Standards, NFPA 257 and are certified by National Accreditation and Management Institute (NAMI) as window assemblies.

• Graffiti Resistant

Glass Block resists damage and is easy to clean.

• Noise Resistant

Glass Blocks thick faces provide great sound resistance.

• Vision Control

Glass Blocks provide a range of visibility depending on pattern chosen.

• Light Transmission

Glass Blocks allow varying degrees of light transmission.

• Design Flexibility

The wide variety of styles and patterns and functional benefits allow for endless design options.

• Security

Glass Blocks enhance the security of your building

Application Uses

Fire Rated Glass Block and Bricks can be used in Residential, Institutional and Commercial buildings.

Typical Applications are:

- Multi-Unit Housing • Stairwells
- Limited Lot Line • Windows
- Communities • Other Fire Rated uses.
- Corridors

Notes:

For complete installation details, product information, specifications and more information on how to design with Seves Glass Block products, see our Architectural Products Brochure or visit our website at www.sevesglassblockinc.com



Fire-Rated Glass Block Window Assemblies

Premiere™ Series Glass Blocks, THICKSET® 60, THICKSET® 90, 3" thick VISTABRIK® and Vetropieno™ Solid Glass Block units have been tested and classified by Underwriters Laboratories (UL-9) and/or NFPA 257 for use in fire-rated window assemblies to panel sizes and dimension limitations as listed.

Masonry Wall Construction						Non-Masonry Wall Construction				
Panel Limitations			Fire Rating			Panel Limitations			Fire Rating	
Product	Max. Area / Panel	Max Ht. or Width	45 Min.	60 Min.	90 Min.	Product	Max. Area / Panel	Max Ht. or Width	45 Min.	60 Min.
Thinline® Series	120 sq. ft.	12 ft.	◆			Thinline® Series	94 sq. ft.	10.75 ft.	◆	
Premiere™ Series	120 sq. ft.	12 ft.	◆			Premiere™ Series	94 sq. ft.	10.75 ft.	◆	
THICKSET® 60	100 sq. ft.	10 ft.	◆	◆		THICKSET® 60	94 sq. ft.	10.75 ft.	◆	◆
THICKSET® 90	100 sq. ft.	10ft.	◆	◆	◆*	THICKSET® 90	94 sq. ft.	10.75 ft.	◆	◆
VISTABRIK®	100 sq. ft.	10 ft.	◆	◆	◆*	VISTABRIK®	94 sq. ft.	10.75 ft.	◆	◆
Vetropieno™	100 sq. ft.	10 ft.	◆	◆	◆*	Vetropieno™	94 sq. ft.	10.75 ft.	◆	◆

* 1/4" steel channel, 3/4" thick expansion material at head and jambs, and fire retardant sealant are required.